



Meinberg Funkuhren

Lange Wand 9

31812 Bad Pyrmont, Germany Phone: +49 (5281) 9309-0 Fax: +49 (5281) 9309-30 https://www.meinbergglobal.com

info@meinberg.de

ECBA32: DCF77 Radio Clock

DCF77 radio controlled clock ECBA32 with 8 bit parallel interface (ECB)

DCF77 radio clock ECBA32 with 8 bit parallel interface (ECB), fast data transmission with FIFO memory, I/O address decoder, programmable address range and periodic interrupts

Important Note

This product is no longer available. We will of course continue to provide support for units that have already been purchased and are still in use. Please contact our [1] Sales Team for further details.

Key Features

- Periodic Interrupts
- 2,5mm LED-display
- ECB Bus Interface
- Reception status indicated by LED
- Buffered hardware clock
- I/O Address Decoder, Programmable Address Area
- High speed data transfer (FIFO buffered)



Characteristics

Receiver Type	Narrowband synchronous receiver with automatic gain control, Bandwidth: approx. 40Hz
Status Indicators	Modulation and field strength visualized by LEDs Free running state visualized by LED after switching to free running quartz clock mode
Type of Antenna	DCF77 indoor antenna AI01
Display	8 digit 7-segment LED display (2.5mm) for time or date (switch-selectable)
Synchronization Time	2
Accuracy free run	Accuracy of the quartz base after min. 24hrs of synchronized operation: ±1·10-6
Reception Monitoring	Incoming time string undergoes multiple checks Plausibility test using two full consecutive time strings
Pulse Outputs	Pulse per second (PPS) and pulse per minute (PPM). TTL level, pulse width: 200 msec
Interface	ECB-bus
Serial Time String Output	2 BCD-bits per byte
Dimensions of the front panel	4HP/3U (20mm x 128mm)
Electrical Connectors	64-pin rear VG edge connector DIN 41612 SMB male connector
Backup Battery Type	In case of supply voltage failure the on-board RTC keeps the time based on XTAL for more than 150 hours (buffer capacitor) Optional: lithium backup battery (life time: 10 years)
Operating Voltage	+5 V DC
Current Draw	ca. 120 mA
Board Type	Eurocard
Board Dimensions	160 mm x 100 mm, 1,5 mm Epoxy
Supported Temperature	Operational: 0 - 50 °C (32 - 122 °F) Storage: -20 - 70 °C (-4 - 158 °F)
Supported Humidity	Max. 85 % (non-condensing) at 40 °C
Contents of Shipment	Scope of supply includes an active ferrite antenna [2]Al01 and 5m of RG174 coaxial cable with BNC connectors. Optional: [3]AW02 with RG58 and patch cord, other length of cable
Options	set mode with external push-buttons



RoHS Status of Product	This product is not covered by the RoHS Directive.
WEEE Status of Product	This product is not affected by the WEEE directive of the EU.

Manual

There is no online manual available for this product.: [4] Contact us

Links:

- [1] mailto:sales@meinberg.de
- [2] https://www.meinbergglobal.com/english/products/dcf77-indoor-antenna.htm
- [3] https://www.meinbergglobal.com/english/products/dcf77-outdoor-antenna.htm
- [4] mailto:info@meinberg.de