



Meinberg Radio Clocks

Lange Wand 9

31812 Bad Pyrmont, Germany Phone: +49 (5281) 9309-0 Fax: +49 (5281) 9309-30

https://www.meinbergglobal.com info@meinberg.de

GPS167TGP: GPS Satellite Receiver in Propac Desk Top Case

GPS Satellite Receiver in Propac Desk Top Case GPS167TGP

GPS Satellite Receiver in Propac Desk Top Case GPS167TGP with Frequency Output, 2 RS232 Interfaces, 2 Time Trigger Inputs and Error Output

Important Note

This product is no longer available and may have been replaced by a newer product. We will, of course, continue to provide support for units that have already been purchased and are still in use. Please contact our [1]Sales Department for further details.

Key Features

- 2 time trigger inputs
- LC-display, 4 x 16 characters
- 2 RS-232 interfaces
- Integrated GPS satellite receiver
- Frequency synthesizer
- Antenna-/converter unit (included)



Characteristics

Receiver Type	6 channel GPS C/A-code receiver
Type of Antenna	Included [2]GPSANTv2 antenna with innovative downconverter technology that allows transmission routes of up to 300 m using RG58 cable, 700 m using RG213 cable, and 1100 m using H2010 Ultraflex cable
Display	LC Display, 4 x 16 characters
Interface	Two independent serial RS-232-interfaces, menu configurable
Serial Time String Output	Baud rate: 300, 600, 1200, 2400, 4800, 9600, 19200 Baud Data format: 7N2, 7E1, 7E2, 8E1, 8N1, 8N2 Time telegram: [3]Meinberg Standard Time String, SAT, Uni Erlangen (NTP), SPA, Sysplex, RACAL, NMEA0183 (RMC,GGA,ZDA), Meinberg GPS, COMPUTIME, ION oder [4]Capture String
Time-Trigger inputs	Resolution: 100 nsec, triggered by falling TTL slope Time of trigger event readable via RS232-interface
Alarm output	Synchronous state of the module, relay output (changeover contact)
Antenna Connector	Type-N connector
Form Factor	Desktop housing, Schroff Propac
Physical Dimensions	260mm x 160mm x 320mm
Supported Temperature	Operational: 0 - 50 °C (32 - 122 °F) Storage: -20 - 70 °C (-4 - 158 °F)
Supported Humidity	Max. 85 % (non-condensing) at 40 °C
Contents of Shipment	GPS antenna/converter unit 20m of cable RG58 with N-type connectors
RoHS Status of Product	This product is fully RoHS-compliant.
WEEE Status of Product	This product is handled as a B2B (Business to Business) category product. To ensure that the product is disposed of in a WEEE-compliant fashion, it can be returned to the manufacturer. Any transportation expenses for returning this product (at end-of-life) must be covered by the end user, while Meinberg will bear the costs for the waste disposal itself.

Manual

The English manual is available as a PDF file: [5] Download (PDF)

Links:

- [1] mailto:sales@meinberg.de
- $\hbox{\cite{thm}$} \begin{tabular}{l} [2] \label{thm:convergence} \begin{t$
- [3] https://www.meinbergglobal.com/english/specs/timestr.htm
- [4] https://www.meinbergglobal.com/english/specs/capstr.htm
- [5] https://www.meinbergglobal.com/download/docs/manuals/english/gps167tgp.pdf