



Meinberg Funkuhren

Lange Wand 9

31812 Bad Pyrmont, Germany Phone: +49 (5281) 9309-0 Fax: +49 (5281) 9309-30 https://www.meinbergglobal.com

info@meinberg.de

TCG511: Time Code Generator (Eurocard)

IRIG or AFNOR time code generator with various outputs

Important Note

This product is no longer available. We will of course continue to provide support for units that have already been purchased and are still in use. Please contact our [1] Sales Team for further details.

This product has been discontinued and has been replaced with: [2]

Key Features

- Unmodulated outputs with TTL, RS232 and RS422 level
- Status LED
- Time information coded in IRIG-A/B or AFNOR format
- Controlled by GPS161/GPS164/GPS167 or PZF511
- High accurate sinewave carrier for modulated output
- Optional onboard diplexer with 4 outputs



Description

The board TCG511 has been designed for the generation of IRIG and AFNOR standard time codes. Particularly it is intended for operation with the Meinberg GPS receivers and our DCF77 correlation receiver. Apart from the digitally generated amplitude-modulated code the TCG511 also provides the unmodulated DC level shift code. The modulated sine wave carrier and the board's internal time pattern are derived from the radio clock's disciplined oscillator. For special applications, the board can be equipped with a freewheeling oscillator (OCXO or TCXO). Signals required for operation are a synchronous pulse per second signal (PPS), a serial time string at RS232 level, and a 10MHz reference clock as mentioned above.

Characteristics

Status Indicators	Synchronous state of time code generator indicated by LED
Input signal	Pulse per second (PPS), active high (TTL level) serial time string (RS232)
Frequency inputs	10MHz oscillator clock (TTL level)
DCLS Timecode Output	TTL into 50 ohm (active low and active high) RS232 (active low and active high) RS422 Open drain transistor output
AM Timecode Output	AM sine wave signal: IRIG: 3Vpp (MARK), 1Vpp (SPACE) into 50 ohm AFNOR: 2.17Vss (MARK), 0.688Vss (SPACE) into 50 ohm
Supported Timecode Formats	A002: 1000pps, DCLS signal, no carrier, BCD time of year A132: 1000pps, AM sine wave signal, 10 kHz carrier, BCD time of year A003: 1000pps, DCLS signal, no carrier, BCD time of year, SBS time of day A133: 1000pps, AM sine wave signal, 10kHz carrier, BCD time of year, SBS time of day B002: 100pps, DCLS signal, no carrier, BCD time of year B122: 100pps, AM sine wave signal, 1 kHz carrier, BCD time of year B003: 100pps, DCLS signal, no carrier, BCD time of year, SBS time of day B123: 100pps, AM sine wave signal, 1kHz carrier, BCD time of year, SBS time of day B123: 100pps, AM sine wave signal, 1 kHz carrier frequency, BCD time of year, year number (099) B126: 100pps, AM sine wave signal, 1 kHz carrier frequency, BCD time of year, year number (099) B007: 100pps, PWM DC signal, no carrier, BCD time of year, SBS time of day, year number (099) B127: 100pps, AM sine wave signal, 1 kHz carrier frequency, BCD time of year, SBS time of day, year number (099) G002: 10000pps, PWM DC signal, no carrier, BCD time of year G142: 10000pps, AM sine wave signal, 100 kHz carrier frequency, BCD time of year G006: 10000pps, PWM DC signal, no carrier, BCD time of year, BCD year G146: 10000pps, AM sine wave signal, 100 kHz carrier frequency, BCD time of year, BCD year IEEE1344: Code according to IEEE1344-1995, 100pps, AM sine wave signal, 1kHz carrier, BCD time of year, SBS time of day, IEEE1344 expansion for date, time zone, daylight saving and leap second in Control Funktions Segment AFNOR: Code according to NFS-87500, 100pps, AM sine wave signal, 1kHz carrier, BCD time of year, complete date, SBS time of day



Dimensions of the front panel	4HP/3U (20mm x 128mm)
Electrical Connectors	64 pin rear VG edge connector DIN 41612
	BNC connector for the sine wave output available in the frontpanel
Operating Voltage	+5 V DC
Current Draw	ca. 300mA
Board Type	Eurocard
Board Dimensions	160 mm x 100 mm, 1,5 mm Epoxy
Supported Temperature	Operational: 0 - 50 °C (32 - 122 °F)
	Storage: -20 - 70 °C (-4 - 158 °F)
Supported Humidity	Max. 85 % (non-condensing) at 40 °C
Warranty	Three-year warranty
Options	Diplexer for modulated signal, four outputs
RoHS Status of Product	This product is fully RoHS-compliant.
WEEE Status of Product	This product is handled as a B2B (Business to Business) category product. To ensure that the product is disposed of in a WEEE-compliant fashion, it can be returned to the manufacturer. Any transportation expenses for returning this product (at end-of-life) must be covered by the end user, while Meinberg will bear the costs for the waste disposal itself.

Manual

The English manual is available as a PDF file: [3] Download (PDF)

Links:

- [1] mailto:sales@meinberg.de
- [2] https://www.meinbergglobal.com/english/archive/TCR180.htm
- $\hbox{[3] https://www.meinbergglobal.com/download/docs/manuals/english/tcg511.pdf}$